

Apache Double Roman Roof Tile

Profile Information & Specifications





Details

Description: Classic, versatile & ageless

Dimensions: 420mm x 332mm

Linear Cover: 300mm
Weight of tile: 4.6kg

Specifications

| Roof Pitch: | 17.5° to 25° | 26° and up |
|-----------------------|--------------|------------|
| Headlap (min.): | 100mm | 75mm |
| Batten Centres (min): | 320mm | 345mm |
| Batten per m²: | 3.13mm | 2.9mm |
| No. of tiles per m²: | 10.42 | 9.66 |
| Mass of tiles per m²: | ±44.8kg | ±41.5kg |
| | _ | |

Tiling Batten: Batten +14mm

Rafter Centres: 760mm with 38 x 38 batten

1000mm with 38 x 50 batten on edge

Colours available:



2-Tone Tan



2-Tone Red



Brown



Charcoal



Tan



2-Tone Terracotta



Red

Perfect for: Residential, Office Parks, Industrial







Apache Tuscan Roof Tile

Profile Information & Specifications





Colours available:



Tan



Charcoal



Terracotta



2-Tone red



2-Tone tan



2-Tone Terrcotta

Details

Description: Classic & elegant **Dimensions:** 420mm x 332mm

Linear Cover: 300mmWeight of tile: 4.9kg

Specifications

| Roof Pitch: | 17.5° to 25° | 26° and up |
|-----------------------|--------------|------------|
| Headlap (min.): | 100mm | 75mm |
| Batten Centres (min): | 320mm | 345mm |
| Batten per m²: | 3.13mm | 2.9mm |
| No. of tiles per m²: | 10.42 | 9.66 |
| Mass of tiles per m²: | ±51kg | ±47kg |

Tiling Batten: Batten +14mm

Rafter Centres: 760mm with 38 x 38 batten

1000mm with 38 x 50 batten on edge

Perfect for: Residential, Office Parks, Industrial







Apache Shingle Roof Tile

Profile Information & Specifications





Details

Description: Stylish & modern **Dimensions:** 420mm x 332mm

Linear Cover: 300mm
Weight of tile: 5.1kg

Specifications

| Roof Pitch: | 17.5° to 25° | 26° and up |
|-----------------------|--------------|------------|
| Headlap (min.): | 100mm | 75mm |
| Batten Centres (min): | 320mm | 345mm |
| Batten per m²: | 3.13mm | 2.9mm |
| No. of tiles per m²: | 10.42 | 9.66 |
| Mass of tiles per m²: | ±52.5kg | ±49.3kg |

Tiling Batten: Batten +14mm

Rafter Centres: 760mm with 38 x 38 batten

1000mm with 38 x 50 batten on edge

Colours available:



Red



Tan



2-Tone Tan



Dolomite



Terracotta



2-Tone Red



Brown



Charcoal



Terracotta

Perfect for: Residential, Office Parks, Industrial







Fixing Specifications: Specification A

Terrain Type:

Terrain with numerous large, high and closely spaced obstructions. This category includes large city centres. Mechanically fix two course of tiles at eaves, verges, ridges and one adjacent full tile at valleys, hips and abutments by nailing or wiring as required.

Roof Pitch:

17.5° to 26° Under tile membrane (*Mandatory*)

26° up to 45° Under tile membrane (*Recommended*)

45° up to 55° Under tile membrane (*Recommended. Each tile to be nailed and clipped*)

55° up and upwards Under tile membrane (Recommended. Each tile to be nailed and clipped)

Fixing Specifications: Specification B

Terrain Type:

Terrain with numerous closley spaced obstruction, the size of domestic houses. Includes well-wooded areas, subrubs, towns and industrial areas. Mechanically fix a band of tiles, equal to a fifth of the number of courses on the rafter length, at eaves and verges or the full overhang, whichever is greater, and at ridges and abutments. Fix one full tile adjacent to hips and valleys and every third tile on the rest of the roof. Cut tiles at hips, valleys and abutments must be secured by nailing or wiring. Soffits must be closed at eaves and verge overhangs.

Roof Pitch:

17.5° to 26° Under tile membrane (*Mandatory*)

26° up to 45° Under tile membrane (*Recommended*)

45° up to 55° Under tile membrane (Recommended. Each tile to be nailed and clipped)

Fixing Specifications: Specification C

Terrain Type:

Exposed open terrain with a few or no obstructions, like open sea coasts and flat, treeless plains with little vegetation. Mechanically fix each tile, soffits must be closed at eaves and overhangs.

Roof Pitch:

17.5° to 45° Under tile membrane (Mandatory. Each tile to be nailed and clipped)

45° up to 90° Under tile membrane (Mandatory. Each tile to be nailed and clipped)

Tile Fittings & Sundries









Colours available



Get in touch

- 2 +267 390 2306 / 7447 4291
- ⊠ sales1@apache.co.bw
- Nkoyaphiri Mogoditshane, Gaborone, Botswana





